



Product Features

- **Simplified Navigation for Enhanced Workflow**
With intuitive icons and controls, the XScribe user interface streamlines workflow from pre-test to recovery, which can reduce staff learning curves. Data is displayed on a 24-inch colour touchscreen display.
- **Wireless ECG Acquisition and Transmission**
The optional Wireless Acquisition Module (WAM™) digitally transmits diagnostic quality 12-lead ECG data, eliminating the need for direct patient connection which is especially important during stress echo evaluations.
- **Advanced VERITAS™ Signal Processing**
Mortara's VERITAS signal processing algorithms provide exceptional accuracy in beat detection and noise rejection, resulting in superior identification of events for both adult and paediatric patients.
- **Comprehensive Presentation of Clinical Data**
XScribe presents continuous ST trends and profile, ST level and slope for all 12 average complexes, and auto comparison with reference complexes.
- **Unique Source Consistency Filter**
Our innovative approach to noise and baseline artifact reduction ensures signal quality, while preserving the integrity of the ECG tracing.
- **Enhanced Full Disclosure Mode**
Continuous beat by beat storage of waveforms and events allows for retrospective review and post-test inclusion within the final report.
- **Report Export and Network Options**
Highly customisable final reports can be manually or automatically exported for long-term storage.
- **Connectivity and Interoperability**
XScribe is designed for simplified integration into EHR systems, minimising manual steps such as data entry and automating electronic charting of the report. Integration technologies include PDF, XML plus bidirectional HL7 and DICOM®.



XScribe™ System Specifications

Scalable, integrated solutions for cardiac stress testing

Features	Specifications
Computer model	HP rp 5800 CPU or later
Processor	Intel® Core™ i3
Graphics	1920 x 1080 or 1920 x 1200
Ram	4 GB
Operating system	Microsoft® Windows® 10 Pro 64-bit
Hard drive capacity	500 GB
Archive	Network or external USB drive
Input devices	Standard keyboard and scroll mouse
Software installation	CD-ROM or USB
Network	100 Mbps connection or better
Front-end ECG devices	WAM for wireless ECG acquisition and TTL/analog output AM12™ for wired ECG acquisition and TTL/analog output
Printing devices HP	M401dn Laser printer (recommended) Z200+ thermal printer (requires additional network port)
USB ports	2 Free USB 2.0 ports
Serial ports	2 Serial ports required for digital interface (a serial-to-serial connection is required)
Audio	Required for NIPB and Pharmacological notification
Isolation transformer required when workstation is used for stress testing	
Isolation transformer requirement	Known Agency Mark (KAM) Meets IEC 60601-1 requirements Protective Earth conductor for all connected equipment Z200+ only configuration: 300 watts LaserJet printer configuration: 1,000 watts
Feature server minimum specifications*	
Processor	Performance equivalent to an Intel Xeon class, Quad-core with hyperthreading
Graphics	1024 x 768
Ram	4 GB
Operating system	Microsoft Windows 2008 or 2012 server R2, 64-bit
System disk	100 GB for OS and product installation (RAID recommended for data redundancy)
Data disks	550 GB hard drive space available HD controller with 128 Mb Read/Write Cache (Raid Recommended For Data Redundancy)
Archive	Network or external USB drive
Software installation	CD-ROM or USB
Network	100 Mbps connection or better
Input devices	Standard keyboard and mouse, optional devices available



Hillrom™

To learn more, contact your Hillrom representative or call Hillrom Customer Care on 1800 445 576.

Always read the labels and instructions for use. Contact your Hillrom Representative for the latest version.

AUTHORISED AUSTRALIAN SPONSOR Welch Allyn Australia Pty Limited
Suite 4.01, 2 Lyonpark Road, Macquarie Park NSW Australia 2113

© 2021 Welch Allyn Australia Pty Ltd. APR234403-AU_r1 01-06-2021 EN/AU

hillrom.com.au

